# The LANL ADVANCED ACCELERATOR APPLICATIONS PROJECT

# Dale Schrage LANL

Workshop on the Advanced Design of Spoke Resonators

Los Alamos, NM, USA October 7 and 8, 2002





### **AAA PROGRAM**

- Authorized by Congress to begin in fiscal year 2001, the DOE Advanced Accelerator Applications (AAA) program was created to address pressing nuclear issues facing the United States:
  - nuclear energy and waste management concerns
  - declining US nuclear infrastructure
  - global nuclear leadership
- website: http://aaa.lanl.gov/





### **AAA PROGRAM**

- DIRECTION & FUNDING PRESENTLY UNCLEAR
- ADVANCED ACCELERATOR APPLICATIONS PROGRAM MAY BECOME "ADVANCED FUEL CYCLES PROGRAM"
- OR, THERE MAY BE TWO SEPARATE PROGRAMS
- DECISION WILL BE LATER IN FY2003
- PROPOSAL IN US CONGRESS FOR ACCELERATOR DRIVE TEST FACILITY





# ACCELERATOR TRANSMUTATION OF WASTE WHY SPOKE CAVITIES?

- TECHNICAL SUPERIORITY TO DTL & CCDTL
- INDUSTRIAL FABRICATION PROVEN
- COMPARABLE INSTALLED COST
- LOWER OPERATING COST
- HIGHER RELIABILITY





# AAA PROGRAM FY2003 PRELIMNARY PLAN

- CEA/CNRS/DOE COLLABORATION
- DESIGN/BID POWER COUPLER
- DESIGN/SPECIFY ELECTROPOLISHING FACILITY
- ATW STUDY
- NIOBIUM STUDY w/JLAB & UVA
- INFORMAL COLLABORATION WITH ANL
- INFORMAL COLLABORATION WITH INFN





## CEA/CNRS/DOE COLLABORATION

#### • ELLIPTICAL CAVITIES:

– DESIGN/PROCURE/TEST  $\beta$  = 0.5, 5-CELL, 704.4 MHz CAVITIES (2ea)


#### • SPOKE CAVITIES:

- CONTINUE TESTS OF EXISTING CAVITIES:
  - LANL:  $\beta = 0.175$ , 2-GAP, 350 MHz CAVITIES (2ea)
  - CNRS:  $\beta = 0.34$ , 2-GAP, 352.2 MHz CAVITY
- DESIGN/ $\beta$  = 0.125, 5-CELL, 350 MHz CAVITIES (2ea)
- PROCURE/TEST  $\beta$  = 0.125, 5-CELL, 350 MHz CAVITIES (2ea) in FY2004 & FY2005





### $\beta = 0.125, 5$ -GAP, 350 MHz CAVITY







# DESIGN/BID POWER COUPLER

- FABRICATE IN INDUSTRY
- BID IN June 2003, AWARD IN October 2004
- OPTIMIZED FOR ATW REQUIREMENTS
- PRELIMINARY REQUIREMENTS
  - **20 mAmps**
  - $-\beta = 0.175 \text{ (2-Gaps)} \beta = 0.34 \text{ (3-Gaps)}$
  - $E_{acc} = TBD (\sim 8 Mvolt/meter)$
  - Power ~ 30 Kwatts





# DESIGN/SPECIFY ELECTROPOLISHING FACILITY

- OBJECTIVE IS TO IMPROVE PERFORMANCE OF ELLIPTICAL CAVITIES
- DESIGN & SPECIFY IN FY2003
- PROCURE & INSTALL IN FY2004
- OPERATE IN FY2005





### **ATW STUDY**

- PERFORM LIMITED SCOPE TRADE STUDY TO CONSIDER SPOKE CAVITIES
  - @  $\beta \sim 0.6$
  - Collaboration with RIA Project





# NIOBIUM STUDY w/JLAB & UVA

- 3-YEAR PROGRAM IN COLLABORATION WITH JLAB & UVA TO IMPROVE THE PROPERTIES OF NIOBIUM
- EMPHASIS ON IMPROVING THE MANUFACTURING PROCESSES TO IMPROVE BATCH-TO-BATCH CONSISTENCY





### 6-YEAR PLAN

TASK	FY2003	FY2004	FY2005	FY2006	FY2007	FY2008
Lab Operations	Level of Effort	Level of Effort	Level of Effort	Level of Effort	Level of Effort	Level of Effort
DOE/CEA/CNRS Collaboration	<ul> <li>Final Lab Tests of β=.175 Spoke Cavity</li> <li>Des/Bid β=.125 Spoke Cavity</li> <li>Des/Bid Power Coupler for β=.125 Spoke Cavity</li> <li>Des/Bid β=.47 Elliptical Cavity</li> </ul>	<ul> <li>Procure β=.125         Spoke Cavities</li> <li>Procure Power         Coupler for         β=.125 Spoke         Cavities</li> <li>Procure β=.47         Elliptical Cavities</li> <li>Design β=.60         Elliptical Cavity</li> </ul>	<ul> <li>Lab Test of β=.125 Spoke Cavities</li> <li>Lab Test of Power Coupler for β=.125 Spoke Cavities</li> <li>Lab Test of β=.47 Elliptical Cavities</li> <li>Procure β=.60 Elliptical Cavities</li> <li>Concept of Cryostat for β=.175 Spoke Cavities</li> </ul>	<ul> <li>Lab Test of β=.60         Elliptical Cavities</li> <li>Concept of         Cryostat for         β=.125 Spoke         Cavities</li> <li>Concept of         Cryostat for β=.47         Elliptical Cavities</li> </ul>	<ul> <li>Concept of         Cryostat for β=.60         Elliptical Cavities</li> <li>Des/Proc Cold         Test of Power         Coupler for β=.125         Spoke Cavities</li> </ul>	• Cold Test of Power Coupler for β=.125 Spoke Cavities
Power Couplers	<ul> <li>Des/Bid Power         Coupler for         β=.175 Spoke         Cavity</li> </ul>	• Procure Power Coupler for β=.175 Spoke Cavities	• Lab Test of Power Coupler for β=.175 Spoke Cavities	Des/Bid Power     Coupler for β=.60     Elliptical Cavities	<ul> <li>Des/Proc Cold         Test of Power         Coupler for β=.175         Spoke Cavities</li> <li>Proc Power         Coupler for β=.60         Elliptical Cavities</li> </ul>	<ul> <li>Cold Test of Power Coupler for β=.175 Spoke Cavities</li> <li>Lab Test of Power Coupler for β=.60 Elliptical Cavities</li> </ul>
Lab Improvements	Study Epolish     System	Proc/Install     Epolish System	<ul> <li>Test Epolish         System with APT         Cavities</li> <li>Des/Specify Heat         Treat System</li> </ul>	Proc/Install Heat Treat System	Test Heat Treat     System with APT     Cavities	•
ADS Optimization	• Study β=.60 Spoke Cavity	Des RF-focussed Spoke Cavity	<ul> <li>Beam Dynamics of ADS Linac</li> <li>Proc RF-focussed Spoke Cavity</li> </ul>	<ul> <li>ADS System         Concept</li> <li>Lab Test of RF-         focussed Spoke         Cavity</li> <li>Lab Test of High         Gradient Spoke         Cavities</li> </ul>	<ul> <li>ADS System         Concept</li> <li>Lab Test of High         Gradient Spoke         Cavities</li> <li>Lab Test of High-         Gradient Elliptical         Cavities</li> </ul>	<ul> <li>ADS System         Concept</li> <li>Lab Test of High         Gradient Spoke         Cavities</li> <li>Lab Test of High-         Gradient Elliptical         Cavities</li> </ul>



